

## Juntas de goma estándar



**Materiales**

Caucho natural NR/nitrilo NBR.  
Caucho cloropreno CR/cedular EPDM.

**Certificados y normas aplicables**



**Temperatura de trabajo**

NR/NBR: -40°C hasta +90°C.  
CR/EPDM: -30°C hasta +120°C.

### Rosca PG

Referencia	PG DIN 40430	D1 Ø mm	D2 Ø mm	H mm	Material	Embalaje unidades
804.0700.0	PG 7	10,7	5	5,0	CR/EPDM	100
804.0700.1			7			
804.0900.0	PG 9	13,3	7	5,5	CR/EPDM	100
804.0900.1			9			
800.1100.0	PG 11	16,5	9	6,0	NR/NBR	100
800.1100.2			11			
800.1300.0	PG 13,5	18,3	11	6,0	NR/NBR	100
800.1300.3			13			
800.1600.2	PG 16	20,4	11	7,0	NR/NBR	100
800.1600.0			13			
800.1600.3			15			
800.2100.1	PG 21	25,9	16	8,0	NR/NBR	100
800.2100.0			18			
800.2900.0	PG 29	34,7	27	9,5	NR/NBR	100
800.2900.3			29			
800.4200.0	PG 42	51,7	40	14,0	NR/NBR	50